




## Fume Hood



LED Display



Waterproof Socket



Water&Gas Remote Control



Double Layer  
1.2mm sheet metal surface,  
melamine board inners

## ADVANTAGE

1. UV lamp for sterilization.
2. resistant to weak acid and alkali.
3. Adjustable air speed: 9 levels.
4. Motorized front window, height adjustable.
5. Microprocessor control system, LED display.
6. With memory function in case of power-failure.

## TECHNICAL PARAMETERS

Model	FH1000(A)	FH1200(A)	FH1500(A)	FH1800(A)
External Size (W*D*H)	1040*800*2200mm	1240*800*2200mm	1540*800*2200mm	1840*800*2200mm
Internal Size (W*D*H)	820*670*730mm	1020*670*730mm	1320*670*730mm	1620*670*730mm
Work Surface Height	850mm			
Max Opening	520mm			
Air Velocity	0.3-0.8m/s			
Noise	≤60dB			
Exhaust Duct	PVC, Standard length: 4 meters, Φ300mm			
LED Lamp	8W*1	12W*1	16W*1	16W*1
UV Lamp	Emission of 253.7 nanometers for most efficient decontamination			
Blower	Built-in centrifugal blower; Speed adjustable			
Front Window	5mm toughened glass; Motorized; Height adjustable			
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Consumption	400W	400W	500W	500W
Material	Exterior	Cold-rolled steel with anti-bacteria powder coating		
	Interior	High grade melamine board with good acid and alkali resistance function		
	Work Table	Chemical resistant phenolic resin		
Standard Accessories	UV lamp*2, LED lamp, Water tap, Gas tap, Water sink, Base cabinet 4 meter PVC exhaust duct, pipe strap*2			
Optional Accessory	Active carbon filter			
Gross Weight	289kg	317kg	350kg	400kg
Package	Main Body	1180*990*1690 mm	1390*990*1690 mm	1690*990*1690mm
	Base Cabinet	1290*990*980mm	1390*990*980mm	1690*970*970mm
				1990*990*980mm